



For health, relaxation and fun!

@ease In-Line System



Video Orientation

START-UP (Fresh Fill)

- 1) Double check that drain cap is securely fastened. Remove filters and fill hot tub with hose placed in filter compartment. Once filled, replace filters and attach the holder over the Jacuzzi filter that does **NOT** have the grid underneath.
- 2) Supply power to hot tub by turning on breaker. Note: Power supply should always be turned off to tub when draining or filling.
- 3) With Jets ON, add **SpaFrog Jump Start** packet to the water (one packet per 600 gallons). Allow jets to run for approximately 10 minutes to dissolve.
- 4) Remove the **Blue @ease Mineral Cartridge** from the box and place in **BOTTOM** slot of filter holder. This cartridge will last 4 months.
- 5) Set the dial on bottom of Silver **@ease SmartChlor Cartridge** per Chart. Then place the **Silver @ease SmartChlor Cartridge** in the **TOP** slot of filter holder. This cartridge will last 2-4 weeks.
@ease SmartChlor Chart
200-299 Gallons—Setting 1
300-450 Gallons—Setting 2
451-550 Gallons—Setting 3
551-600 Gallons—Setting 4
- 6) With Jets **OFF**, pour 4oz of **Silk Balance** into filter area.
- 7) Unwrap and place **Scumbug** in filter compartment. Start-up is now complete. Close and lock safety cover. Allow 12-24 hours for water to heat.

Well Water users may be required to bring sample water in for testing for a customized treatment routine

WEEKLY CARE

- 1) KEEP FILTERS CLEAN—Pumps work extra hard when dirty filters restrict water flow and may cause FLO errors, cloudy water, etc. Remove and clean filters with high pressure nozzle provided.
- 2) With jets **OFF**, pour 4oz of **Silk Balance** into filter area.
- 3) Replace the **Silver @ease SmartChlor Cartridge** every 2-4 weeks.
- 4) When you replace **Silver @ease SmartChlor Cartridge**, (with jets ON) add packet of **Frog Maintain** or **SpaGuard Enhanced Shock** to filter area. Run jets for approximately 10 minutes to dissolve.

REGULAR CARE (as needed)

- 1) Every 4 weeks or so, remove and soak filters in **SpaGuard Filter Cleaner** to remove oils and biofilm.
- 2) Every 1-4 months, clean & condition safety cover per manufacturer guidelines.
- 3) Every 4 months, remove and replace **Blue @ease Mineral Cartridge**.

AUSTIN • 14106 N. IH-35, Austin, TX 78728 • (512)459-9181

DALLAS • 15250 Dallas Pkwy, Dallas, TX 75248 • (214)254-4070

FORT WORTH • 4820 SE Loop 820, Ft Worth, TX 76140 • (817)572-0004

GRAPEVINE • 1419 State Hwy 114W, Grapevine, TX 76051 • (817)481-4288

LEWISVILLE • 310 E Round Grove Rd, Lewisville, TX 75067 • (469)312-6161